

AD-A233 065

ted to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of is burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

Date.		3. Report Type and Dates Covered. Contract	
4. Title and Subtitle. AXKT Drop Rate Test		5. Funding Numbers. Program Element No. 63704N Project No. R01180S Task No. 300 Accession No. DN258017	
6. Author(s). Dan Moffat		8. Performing Organization Report Number. R-2558	
7. Performing Organization Name(s) and Address(es). Sippican Ocean Systems, Inc. P. O. Box 861 Seven Barnabas Road Marion, MA 02738-0861		9. Sponsoring/Monitoring Agency Name(s) and Address(es). Naval Ocean Research and Development Activity* ASW Oceanography Office NSTL, MS 39529-5004	
11. Supplementary Notes. Contract N00014-88-C-6027 *Presently Naval Oceanographic and Atmospheric Research Laboratory Stennis Space Center, MS 39529-5004		10. Sponsoring/Monitoring Agency Report Number. CR 006:91	
12a. Distribution/Availability Statement. Approved for public release; distribution is unlimited.		12b. Distribution Code.	
13. Abstract (Maximum 200 words). A Sippican tank test was performed on the AXKT probe to obtain a first approximation of the descent rate for this probe prior to ocean testing.			
14. Subject Terms. (U) Oceanographic Equipment; (U) Radiance; (U) Optical Instruments		15. Number of Pages. 2	
		16. Price Code.	
17. Security Classification of Report. Unclassified	18. Security Classification of This Page. Unclassified	19. Security Classification of Abstract. Unclassified	20. Limitation of Abstract. SAR

DTIC
ELECTE
MAR 14 1991
S E D

LINE FILE COPY

R-2558

Sippican Inc.

AXKT

Drop Rate Test

Date: Dec. 12, 1989

Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	



Prepared by: Dan Moffat
Dan Moffat

Approved by: Bruce Dalton
Bruce Dalton

Introduction

A Sippican tank test was performed on the AXKT probe to obtain a first approximation of the descent rate for this probe prior to ocean testing.

Personnel

Dan Moffatt
Bruce Dalton

Equipment

Data Precision Data 6000 storage oscilloscope
10 ft. diameter X 30 ft. deep test tank with a moveable floor.
Custom built hydrophone.
10 ft. X 1 in. dia. Aluminum pole.
9 ft. 1/4 in. X 1 in. dia. Aluminum pole.
7 AXKT probes

Procedure

The test setup can be seen in the diagram on page 2.

The floor of the test tank was lowered till the top of the 10 ft. pole was flush with the water surface. The hydrophone was lowered to a depth of 8 feet and connected to the data 6000 oscilloscope. The first three probes were drop into the water nose first from a height of approximately 2 feet above the water surface. The noise of water entry and the impact with the tank floor was recorded on the oscilloscope. The descent times can be seen in the following table.

The 9 ft. 1/4 in. pole was then attached to the 10 ft. pole and the floor lowered till the top of the pole was flush with the water surface. The last 4 probes were then dropped in the same manner as the first 3 and their descent times recorded on the oscilloscope. (See Table Below)

Descent Time

No.	Water Depth Ft.	Time Sec.
1	10	2.111
2	10	2.136
3	10	2.035
4	19.02	3.798
5	19.02	3.856
6	19.02	3.682
7	19.02	3.712

The mean and standard deviation for both water depths are:

10 ft. mean 2.092, and standard deviation 0.055 seconds.
19 ft. mean 3.762, and standard deviation 0.080 seconds.

The descent time for probes was then calculated by:

Descent Time = (19.02 - 10.00) / (3.762 - 2.092)

Descent Time = 5.40 ft/sec or 1.65 m/sec

TEST DIAGRAM

